



Product Code	APC-WHT-5012500WP
Description	Pneumatic Single Piece Slim In-wall Cistern with Wall Mounting Frame, Installation Kit and “P-Type” Drain Pipe Connection Set for Wall Hung WC (without Flush Control Plate)
Flow Rate	3.0/6.0 LPF
Features	<ul style="list-style-type: none"> • Tank body: Strong 80 mm thick High-density polyethylene (HDPE) ‘Single-piece’ body. • Anti-Condensation Lining: Anti condensation lining of 6mm thick wall takes care of temperature change. • Inlet & Outlet Valves: Inlet valve has a special rotary structure which gives out low noise & anti siphon function. Both valves (Inlet & outlet) are WARS approved. • Working Pressure: 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water supply) • Life Cycles of Mechanism: The lifetime of sea water test and dirty water test have passed 100,000 cycles • Flush Control Plates: Toughened glass with ABS made chrome plated push buttons of control plates which is compatible for Single Piece Slim in-wall Cistern (APC-WHT-5012500WP) • Wall Mounted Frame: oxford blue Powder coated steel frame.
Application	<ul style="list-style-type: none"> • For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres • Solid pre-wall installation system for brick & solid walls • For installation in a load bearing stud wall. • Not suitable for installation in a drywall

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.