



| | |
|---|---|
| Product Code | TIA-CHR-73681N |
| Description | In-wall thermostatic shower valve with 2-way diverter |
| Flow Rate | 40.63 LPM @ 3 bar |
| Recommended Water Pressure | 1.0 Bar - 5 Bar |
| Brass Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| Cartridge Specification | <ul style="list-style-type: none"> Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure High technology thermoplastic polymer minimises lime-scale build up Standard temperature range: 15° C to 60° C (59-104°F) Shower mixer contains ceramic cartridge for divert water in two outlets. Protected against backflow |
| Finish | Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (600 hrs + Validated) Adhesion (Pass) |
| Available Colour Finishing | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite (GRF), Stainless Steel Finish (SSF), Gold Bright PVD (GBP), Glod Matt PVD (GMP), Black Pearl PVD (BLP) & Blush Gold Bright PVD (BGP). |
| * As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy | |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |